data sheet

+AE102SSU_ALU
ANTARES - EASY

Dimensions

Safety area	Impact area	Falling height HIC	Physical footprint	Number of users
14 x 11,7 m	65 mq	190 cm	10 x 8,2 x 3,5 m	25

Characteristics

2 hdpe

stainless steel screws

use under surveillance

Age range

3-12

Materials

anodised aluminium

Made of EN EV6060 anodized alumium 9x9cm custom mold with rounded edges, minimum thickness 2,7mm

inclusive

Manufacturer

Pozza 1865 S.R.L.

Country of manufacturing

ITALY

Plan



Picture

Components list



xABACOGT-01_E_ALU - NG OXO Panel Easy
N. 1 Two colored polyethylene panel with serigraphy XOX symbols, 9 half-moon rolling panels, Inox steel bolts.

xBV-10_E_ALU - NG Braille Panel Easy
NR 1 .

xBV-7_E_ALU - NG Shop panels Easy
N. 2 Vertical panel made of polyethylene and wood shelf.

xP-2_E _ALU - NG Protection lateral panels with polycarbonate portholes Easy
N. 1 Made of polyethylene, with polycarbonate portholes, provided with stainless steel brackets for fixing them to the tower.

xP-7.1_E_ALU - NG Simple Skyblue Panel
N. 2 .

xP-7_E _ALU - NG Green Panel
N. 2 .

xPAL-01_ALU - NG Angular Gym
N. 1 Vertical net with frame made of lamellar wood beams fixed through disappearing and passing nuts and bolts Bars realized with stainless steel tubular pegs, mounted into two lateral wooden supports Climbing cord

xPAL-04b_ALU - NG Climbing
N. 1 Made with stainless steel rugs and recycled material base with resin climbing rocks

xPI-10_E_ALU - NG Fixed inclined bridge Easy
N. 3 Walkway made of impregnated wood, with polyethylene parapets

xPI-6_E_ALU - NG Tibetan bridge Easy
N. 2 The net is made of steel strands rope, 18 mm diameter, covered with a colored nylon braid, highly resistant. The knots are covered with shell-shape protections.

xPP-14_E_ALU - NG Fireman pole h 140 cm Easy
N. 1 Made of tubular stainless steel

xPR_E_ALU - NG Easy Railing
N. 2 Fantasy railing in painted steel

xPS-14_E_ALU - NG Spiral perch h 140 cm Easy
N. 1 Composed bystainless steel tubular, support bracket and locking handles in painted steel

xQ-4_E_ALU - NG Square tower h 40 cm Easy (without roof)
N. 1 Composed of 4 posts having a 9 x 9 cm section aluminium, 1 square platform placed at a height of 90 cm.

xQ-9_E_ALU - NG Square tower without roof h90 cm Easy
N. 3 Composed of 4 posts having a 9 x 9 cm section aluminium, 1 square platform placed at a height of 90 cm.

xQT12-14_E_ALU - NG Easy Square tower h140 cm
N. 1 Composed by 4 posts having a 9 x 9 cm section by aluminium, 1 square platform placed at a height of 140 cm. Roof made of painted steel tubes.

xQT12-9_E_ALU - NG Easy Square tower h90 cm
N. 1 Composed by 4 posts having a 9 x 9 cm section by aluminium, 1 square platform placed at a height of 90 cm. Roof made of painted steel tubes.

xQT4-14_E_ALU - NG Square tower h140 cm Easy
N. 1 Composed by 4 posts having a 9 x 9 cm section by aluminium, 1 square platform placed at a height of 140 cm. Coloured polyethylene gable roof.

xQT4-9_E_ALU - NG Square tower h90 cm style Easy
N. 1 Composed by 4 posts having a 9 x 9 cm section by aluminium, 1 square platform placed at a height of 90 cm. Coloured polyethylene gable roof.

xS6-14_E_ALU - NG Shroud lift h140 cm Easy
N. 1 Composed by climbing net in steel rope. Included by thrust bar

xS-9_E_ALU - NG Climbing ladder h90 cm Easy
N. 1 made of aluminium, complete with handrails and protective panels made of polyethylene.



xSCL2-4_ALU - NG Climbing Platform h40 cm
N. 1 .

xSTI-14_E_ALU - NG Descending tube slide h 140 cm Easy
N. 1 .

xSTI-9_E_ALU - NG Descending tube slide h90 cm Easy
N. 1 .

xSVPX-14_E_ALU - NG Straight slide h140 cm Easy
N. 1 Easy slide with lateral sides made of polyethylene and stainless steel slide certified according to the existing rules; starting platform height 140 cm; provided with a transversal bar.

xSVPX-9_E_ALU - NG Straight slide h90 cm Easy
N. 1 Easy slide with lateral sides made of polyethylene and stainless steel slide certified according to the existing rules; starting platform height 90 cm; provided with a transversal bar.



xTT-17_E_ALU - NG Polyethylene Tunnel Easy
N. 2 Made of polyethylene provided with panels of connection to polyethylene turrets

METODO DI FISSAGGIO A TERRA DEI MONTANTI DEL GIOCO: Attrezzatura predisposta per fissaggio a terra mediante l'utilizzo di appositi telai metallici.

INFORMAZIONI RELATIVE ALL'ISPEZIONE: Ispezione visiva periodica - Controllo della pulizia dell'attrezzatura - Controllo degli interspazi tra terreno ed attrezzatura - Controllo della consistenza del terreno - Controllo delle fondamenta - Controllo degli spigoli - Controllo dell'eventuale mancanza di parti - Controllo dell'usura eccessiva delle parti mobili (snodi e boccole) - Controllo dell'integrità dell'intera attrezzatura. Per le aree gioco soggette ad uso intensivo o vandalismo può essere necessaria un'ispezione giornaliera. Ispezione annuale periodica: Potrebbe rendersi necessario lo smontaggio di alcune parti per la verifica

Copyright (C) POZZA 1865 S.r.l. - P.IVA IT02311670224 - info@pozza.it