


AF604WU

ISCHIA con TUNNEL e SCIVOLO A TUBO


Dimensions					
	Safety area	Impact area	Falling height HIC	Physical footprint	Number of users
	1200 x 1400 cm	51 mq	140 cm	1010 x 830 x 360 cm	15

Characteristics



pine wood


pavimentazione
alveolare

use under
surveillance

5 anni
GARANZIA

Age range

Fino a 12 anni


Materials



legno di pino

Made of CAM compliant wood.

Plan



Picture



Manufacturer

Pozza 1865 S.R.L.

Country of manufacturing

ITALY



Components list



TT6-14 - Triangular tower h 140cm:

NR 1 Composed of 3 posts having a pentagonal section by lamellar wood, 1 square platform placed at a height of 140 cm. Coloured polyethylene gable roof.




QT4-14 - Square tower h 140 cm

NR 2 Manufactured with 4 posts having a 9 x 9 cm section by lamellar wood, 1 square platform placed at a height of 140 cm. Coloured polyethylene gable roof.




QT4-9 - Square tower h 90 cm-1

NR 1 Manufactured with 4 posts having a 9 x 9 cm section by lamellar wood, 1 square platform placed at a height of 90 cm. Coloured polyethylene gable roof.




PD-6 - Tibetan bridge-1

NR 1 The net is made of steel strands rope, 18 mm diameter, covered with a colored nylon braid, highly resistant. The knots are covered with shell-shape protections.




TT-17poly - Polyethylene Tunnel

NR 1 Made of polyethylene provided with panels of connection to polyethylene turrets




PI-5 - Inclined mobile bridge

NR 1 Made of impregnated wood, with laminated wood beams oscillating hanging on to the handrail with steel ropes coated




SVPX-14 - Scivolo h 140 cm

NR 1 Scivolo h140cm realizzato con scivolata in acciaio inox di larghezza 45cm modello inclusive per garantire l'utilizzo assistito e pannelli laterali in polietilene HDPE composto per il 51% di plastica riciclata pannelli laterali di protezione in polietilene e barra reggisplinta di lunghezza 86 cm realizzata in acciaio verniciato. Tutta la bulloneria e gli elementi di fissaggio in acciaio inox



SVPX-9 - Straight slide h 90 cm

NR 1 slide with lateral sides made of polyethylene and stainless steel slide certified according to the existing rules; starting platform height 90 cm; provided with a transversal bar.



SCL1-14 - Free-climbing inclined ramp h. 140

NR 1 H140 Climbing platform - Made of an HDPE panels with anti slip coating, resin climbing holds on top. Support structure made of painted and galvanized steel. All fixing elements made of stainless steel



S-14 - Climbing ladder h 140 cm

NR 1 made of impregnated wood, complete with handrails and protective panels made of polyethylene.



SW-14 - Tube-shaped slide h 140 cm diameter 80 cm

NR 1 Polyethylene slide certified according to the existing rules; starting platform height 140 cm



P-7 - Protection lateral panels

NR 4 Panel made of HDPE polyethylene,
bi-color 86cm in width with drawing on
the outer layer. all the fixing elements in
Stainless steel

METODO DI FISSAGGIO A TERRA DEI MONTANTI DEL GIOCO: Attrezzatura predisposta per fissaggio a terra mediante l'utilizzo di appositi telai metallici.

INFORMAZIONI RELATIVE ALL'ISPEZIONE: Ispezione visiva periodica - Controllo della pulizia dell'attrezzatura - Controllo degli interspazi tra terreno ed attrezzatura - Controllo della consistenza del terreno - Controllo delle fondamenta - Controllo degli spigoli - Controllo dell'eventuale mancanza di parti - Controllo dell'usura eccessiva delle parti mobili (snodi e boccole) - Controllo dell'integrità dell'intera attrezzatura. Per le aree gioco soggette ad uso intensivo o vandalismo può essere necessaria un'ispezione giornaliera. Ispezione annuale periodica: Potrebbe rendersi necessario lo smontaggio di alcune parti per la verifica

ARREDO URBANO GIOCHI PER PARCHI SCENOGRAFIE DAL 1950 ALL'AVANGUARDIA
Copyright (C) POZZA 1865 S.r.l. - P.IVA IT02311670224 - info@pozza.it

www.pozza.it