data sheet

+AF200.PD-6_ALU
KOS CON TIBETANO



Dimensions

Safety area	Impact area	Falling height HIC	Physical footprint	Number of users
6,5 x 6 m	24 mq	140 cm	3,5 x 3 x 1,4 m	15

Characteristics

stainless steel screws

Age range


Da 3 a 12 anni

Materials

anodised aluminium

Made of EN EV6060 anodized alumium 9x9cm custom mold with rounded edges, minimum thickness 2,7mm

Plan



Area di sicurezza totale / Total safety area: 29.5mq
Altezza Max di Caduta / Max falling height: 0.90m

Picture



Manufacturer

Pozza 1865 S.R.L.

Country of manufacturing

ITALY

Components list



xTT-14_ALU - NG Triangular Tower h140 with roof Fantasy
N. 1 .

xG_90X90_90-190_ALU - NG Leg 90x90 from 90 190
N. 2 .



x0454_ALU - NG Platform Joint for Square Posts
N. 1 .



xSCL1-14_ALU - NG Free-climbing inclined ramp h. 140
N. 1 H140 Climbing platform - Made of an HDPE panels with anti slip coating, resin climbing holds on top. Support structure made of painted and galvanized steel. All fixing elements made of stainelss steel



xS4-14_ALU - NG Steel ladder h140 cm
N. 2 Rungs made of stainless steel. Complete with steel bar.



xPD-6_ALU - NG Tibetan bridge-1
N. 1 The net is made of steel strands rope, 18 mm diameter, covered with a colored nylon braid, highly resistant. The knots are covered with shell-shape protections.



xPAL-04b_ALU - NG Climbing
N. 1 Made with stainless steel rugs and recycled material base with resin climbing rocks



xT3_ALU - NG Simple roof Fantasy
N. 1 HDPE Polyethilene roof with stainless steel fixing bracket



xPAL-01C_ALU - NG Net gym
N. 1 Vertical net with frame made of painted steel supporting a climbing net made of steel rope with nylon cover

METODO DI FISSAGGIO A TERRA DEI MONTANTI DEL GIOCO: Attrezzatura predisposta per fissaggio a terra mediante l'utilizzo di appositi telai metallici.

INFORMAZIONI RELATIVE ALL'ISPEZIONE: Ispezione visiva periodica - Controllo della pulizia dell'attrezzatura - Controllo degli interspazi tra terreno ed attrezzatura - Controllo della consistenza del terreno - Controllo delle fondamenta - Controllo degli spigoli - Controllo dell'eventuale mancanza di parti - Controllo dell'usura eccessiva delle parti mobili (snodi e boccole) - Controllo dell'integrità dell'intera attrezzatura. Per le aree gioco soggette ad uso intensivo o vandalismo può essere necessaria un'ispezione giornaliera. Ispezione annuale periodica: Potrebbe rendersi necessario lo smontaggio di alcune parti per la verifica

Copyright (C) POZZA 1865 S.r.l. - P.IVA IT02311670224 - info@pozza.it